NSN 5306-01-175-6919

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-175-6919 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.346 inches and 0.430 inches **Fastener Length:** Between 1.160 inches and 1.190 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Shoulder Diameter:** 0.3115 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 0.740 inches first shoulder and 0.760 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.972 inches first hole and 1.022 inches first hole **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5306-01-175-6919 Shoulder Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0