## NSN 5306-01-175-7573

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-175-7573

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 2.323 inches and 2.353 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 1.990 inches and 2.000 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8735 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, cl2, ty2 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-175-7573

Shear Bolt - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

80205-nas1303 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0