

View Online at <https://aerobasegroup.com/nsn/5306-01-177-5714>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.751 inches

**Fastener Length:**

0.810 inches

**Head Style:**

Spline extended washer

**Head Height:**

0.388 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

0.091 inches

**Head Minor Diameter:**

0.437 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Special Features:**

Dry film lub, mil-I-46010, type 1

**Material:**

Steel

**Material Specification:**

Mil-s-6049 military specification single material response

**Surface Treatment:**

Nickel

**Special Test Features:**

Embrittlement relief, bake 23 hrs, 375 +/- 25 deg

**Surface Treatment Specification:**

Qq-n-290, type 1 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.