

View Online at <https://aerobasegroup.com/nsn/5306-01-177-5714>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.751 inches

Fastener Length:

0.810 inches

Head Style:

Spline extended washer

Head Height:

0.388 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

0.091 inches

Head Minor Diameter:

0.437 inches

Thread Diameter:

0.375 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Special Features:

Dry film lub, mil-I-46010, type 1

Material:

Steel

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Nickel

Special Test Features:

Embrittlement relief, bake 23 hrs, 375 +/- 25 deg

Surface Treatment Specification:

Qq-n-290, type 1 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.