## NSN 5306-01-178-6220

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-178-6220

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 1.017 inches and 1.067 inches  |
| Fastener Length:   |
| Between 13.527 inches and 13.557 inches  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.328 inches and 0.360 inches  |
| Width Between Flats:   |
| Between 0.928 inches and 0.939 inches  |
| Thread Diameter:   |
| 0.625 inches   |
| Grip Length:   |
| Between 12.490 inches and 12.510 inches  |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 140000 pounds per square inch  |
| Product Name:  |
| Navy special project   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5732 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas1010 professional/industrial association standard                                       |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5306-01-178-6220

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0