## NSN 5306-01-179-9436

Machine Bolt - Page 1 of 2

Between 0.740 inches and 0.820 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-179-9436

Head Style: Hexagon  Head Height: Between 0.167 inches and 0.183 inches  Width Between Flats: Between 0.430 inches and 0.439 inches  Hole Diameter: 0.065 inches  Thread Diameter: 0.250 inches  Grip Length:
Head Height: Between 0.167 inches and 0.183 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: 0.065 inches Thread Diameter: 0.250 inches
Between 0.167 inches and 0.183 inches  Width Between Flats:  Between 0.430 inches and 0.439 inches  Hole Diameter:  0.065 inches  Thread Diameter:  0.250 inches
Width Between Flats: Between 0.430 inches and 0.439 inches  Hole Diameter: 0.065 inches  Thread Diameter: 0.250 inches
Between 0.430 inches and 0.439 inches  Hole Diameter: 0.065 inches  Thread Diameter: 0.250 inches
Hole Diameter:  0.065 inches  Thread Diameter:  0.250 inches
0.065 inches  Thread Diameter: 0.250 inches
Thread Diameter: 0.250 inches
0.250 inches
Grip Length:
Between 0.315 inches and 0.375 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
24.0 rockwell c and 35.0 rockwell c
Minimum Yield Strength:
85000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response

## **NSN 5306-01-179-9436** Machine Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig:

A003b0