
NSN 5306-01-179-9444

Machine Bolt - Page 1 of 2





Thread Class: 3a

Thread Direction:

Right-hand

Thread Length:

Between 1.143 inches and 1.220 inches

Fastener Length:

Between 1.203 inches and 1.250 inches

Head Style:

Hexagon

Head Height:

0.281 inches

Width Between Flats:

Between 0.490 inches and 0.502 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Thread Diameter:

0.312 inches

Hole Quantity:

6

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas565 professional/industrial association standard

NSN 5306-01-179-9444

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

