

View Online at <https://aerobasegroup.com/nsn/5306-01-179-9464>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.374 inches and 0.424 inches

Fastener Length:

Between 0.884 inches and 0.914 inches

Head Style:

Spline extended washer

Head Height:

0.178 inches

Width Between Flats:

Between 0.235 inches and 0.250 inches

Extended Washer Diameter:

Between 0.349 inches and 0.359 inches

Extended Washer Thickness:

Between 0.017 inches and 0.037 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Round longitudinal hole

Material:

Steel

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate or aluminum and chromate

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or mil-c-83488, type 2, class 3 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.