

View Online at <https://aerobasegroup.com/nsn/5306-01-179-9464>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.424 inches

**Fastener Length:**

Between 0.884 inches and 0.914 inches

**Head Style:**

Spline extended washer

**Head Height:**

0.178 inches

**Width Between Flats:**

Between 0.235 inches and 0.250 inches

**Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

**Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

**Hole Diameter:**

Between 0.032 inches and 0.042 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Round longitudinal hole

**Material:**

Steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate or aluminum and chromate

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response or mil-c-83488, type 2, class 3 military specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.