

View Online at <https://aerobasegroup.com/nsn/5306-01-180-1726>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.562 inches

Fastener Length:

Between 2.110 inches and 2.140 inches

Head Style:

Double hexagon

Head Height:

0.400 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Shank Unthreaded Hole Diameter:

0.136 inches first hole and 0.146 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

1.563 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

260000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.940 inches first hole

Material:

Steel

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Ams 2416 assn standard 1st treatment response and ams 2416 assn standard 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0