

View Online at <https://aerobasegroup.com/nsn/5306-01-180-4729>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.865 inches and 0.945 inches

Fastener Length:

Between 1.865 inches and 1.885 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.100 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.940 inches and 1.000 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Round

Surface Finish:

63.0 microinches grip

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0