NSN 5306-01-180-9104

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-180-9104

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 1.438 inches and 1.468 inches
Head Style:
Hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Three de Ote Ber had (40%)
Thready Qty Per Inch (tpi):
24
24
24 Min. Tensile Strength (psi):
24 Min. Tensile Strength (psi): 180000 pounds per square inch
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish:
24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name:
24 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material:
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification:
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Product Name: Navy special project Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf

N/a

NSN 5306-01-180-9104

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0