NSN 5306-01-181-0802

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-181-0802

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 1.000 inches and 1.050 inches **Fastener Length:** Between 4.010 inches and 4.040 inches **Head Style:** Spline extended washer **Head Height:** Between 0.373 inches and 0.413 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.102 inches and 0.122 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Head Minor Diameter:** Between 0.610 inches and 0.625 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 2.990 inches and 3.010 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, ty, 2, cl 2 military specification single treatment response **Thread Series Designator:**

Unjf

NSN 5306-01-181-0802

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: