

View Online at <https://aerobasegroup.com/nsn/5306-01-181-0802>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.000 inches and 1.050 inches

Fastener Length:

Between 4.010 inches and 4.040 inches

Head Style:

Spline extended washer

Head Height:

Between 0.373 inches and 0.413 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.102 inches and 0.122 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Head Minor Diameter:

Between 0.610 inches and 0.625 inches

Thread Diameter:

0.562 inches

Grip Length:

Between 2.990 inches and 3.010 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, ty, 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.