

View Online at <https://aerobasegroup.com/nsn/5306-01-182-1630>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.424 inches

**Fastener Length:**

Between 0.759 inches and 0.789 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.158 inches and 0.198 inches

**Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

**Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

**Hole Diameter:**

Between 0.032 inches and 0.042 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Head Minor Diameter:**

Between 0.253 inches and 0.259 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0