NSN 5306-01-182-5633

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-182-5633

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.298 inches and 0.348 inches |
| Fastener Length: |
| Between 1.246 inches and 1.276 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| Between 0.070 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.928 inches and 0.948 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-182-5633

Shear Bolt - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0