NSN 5306-01-182-9109

Shear Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-01-182-9109



3a **Thread Direction: Right-hand Thread Length:** Between 0.485 inches and 0.515 inches Fastener Length: Between 1.235 inches and 1.265 inches Head Style: Double hexagon w/hole **Head Height:** 0.234 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** 0.069 inches Hole Diameter: Between 0.034 inches and 0.042 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches Grip Length: 0.750 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style: Double hexagon flats Material: Steel comp xm-13 **Material Specification:**

Ams5629 assn standard single material response

NSN 5306-01-182-9109

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0