## NSN 5306-01-183-2245

Machine Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.562 inches

**Thread Direction:** 

Fastener Length: 1.156 inches Head Style:

За



View Online at https://aerobasegroup.com/nsn/5306-01-183-2245

| Crowned hexagon                                       |                   |
|---|-------------------|
| Head Height:  |                   |
| Between 0.131 inches and 0.151 inches                 |                   |
| Width Between Flats:                                  |                   |
| 0.490 inches  |                   |
| Hole Diameter:  |                   |
| 0.046 inches  |                   |
| Thread Diameter:                                      |                   |
| 0.250 inches  |                   |
| Grip Length:  |                   |
| 0.594 inches  |                   |
| Hole Quantity:  |                   |
| 1   |                   |
| Hole Type:  |                   |
| Drilled   |                   |
| Thready Qty Per Inch (tpi):                           |                   |
| 28  |                   |
| Min. Tensile Strength (psi):                          |                   |
| 125000 pounds per square inch                         |                   |
| Hardness Rating:                                      |                   |
| 26.0 rockwell c and 32.0 rockwell c                   |                   |
| Hole Configuration Style:                             |                   |
| Hexagon flats   |                   |
| Special Features:                                     |                   |
| Alter from p/n 428h4-12                               |                   |
| Material:   |                   |
| Steel comp 4140                                       |                   |
| Material Specification:                               |                   |
| Mil-s-5626 military specification single material re- | sponse            |
| Surface Treatment:                                    |                   |
| Cadmium   |                   |
| Surface Treatment Specification:                      |                   |
| Qq-p-416 type 2 cl 3 federal specification single t   | reatment response |
|   |                   |
|   |                   |
|   |                   |

## NSN 5306-01-183-2245

Machine Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf                       |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |
| No                        |
| Fiig:                     |
| A003b0                    |

Mil-std (military Standard):

Mil-s-5626 spec.