## NSN 5306-01-183-4005

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-183-4005

80205-nas1958 professional/industrial association standard

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.710 inches and 0.760 inches  |
| Fastener Length:   |
| Between 1.782 inches and 1.812 inches  |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| Between 0.250 inches and 0.265 inches  |
| Width Between Flats:   |
| Between 0.741 inches and 0.752 inches  |
| Grip Diameter:   |
| Between 0.4985 inches and 0.4995 inches  |
| Single Shear Strength:   |
| 108000 pounds per square inch  |
| Thread Diameter:   |
| 0.500 inches   |
| Grip Length:   |
| Between 1.052 inches and 1.072 inches  |
| Thready Qty Per Inch (tpi):  |
| 20   |
| Min. Tensile Strength (psi):   |
| 180000 pounds per square inch  |
| Surface Finish:  |
| 32.0 microinches threads   |
| Product Name:  |
| Navy special project   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |

## NSN 5306-01-183-4005

Shear Bolt - Page 2 of 2



| _ |   |            |   |    |    |
|---|---|------------|---|----|----|
| • | n | <b>0</b> 1 | • | 12 | e: |
|   |   |            |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0