

View Online at <https://aerobasegroup.com/nsn/5306-01-183-6974>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.240 inches and 0.250 inches

Fastener Length:

Between 0.610 inches and 0.640 inches

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

First Diameter From Head:

Between 0.090 inches and 0.100 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.360 inches and 0.400 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c and 45.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-e-14072 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-e-14072 spec.