## NSN 5306-01-183-6977

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-183-6977



## Thread Class:

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 0.365 inches and 0.415 inches

#### Fastener Length:

Between 1.250 inches and 1.280 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.196 inches

#### Width Between Flats:

Between 0.243 inches and 0.251 inches

#### **Extended Washer Diameter:**

Between 0.340 inches and 0.350 inches

#### **Extended Washer Thickness:**

0.064 inches

#### Hole Diameter:

Between 0.034 inches and 0.042 inches

#### **Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

#### **Thread Diameter:**

0.190 inches

#### Grip Length:

Between 0.865 inches and 0.885 inches

#### Hole Quantity:

4

Hole Type:

Drilled

#### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

220000 pounds per square inch

## Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

## Hole Configuration Style:

Double hexagon longitudinal hole

### Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

# NSN 5306-01-183-6977

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0