## NSN 5306-01-184-7695

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-184-7695 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.353 inches **Fastener Length:** Between 1.276 inches and 1.306 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.186 inches and 0.206 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** 0.937 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, cl 2 military specification single treatment response

Unjf

Shelf Life:

**Thread Series Designator:** 

N/a

## NSN 5306-01-184-7695

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.