

View Online at <https://aerobasegroup.com/nsn/5306-01-184-8297>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.498 inches

Fastener Length:

Between 2.248 inches and 2.288 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.374 inches first shoulder

Shoulder Length:

1.760 inches first shoulder and 1.780 inches first shoulder

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

6500 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single material response or ams 6300 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1297 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.