## NSN 5306-01-185-0447

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-185-0447

| View Online at https://aerobasegroup.com/nsn/5306       | 3-01-185-0 |
|---|------------|
| Thread Class:   |            |
| 3a  |            |
| Thread Direction:                                       |            |
| Right-hand  |            |
| Thread Length:  |            |
| Between 0.475 inches and 0.525 inches                   |            |
| Fastener Length:  |            |
| Between 1.547 inches and 1.577 inches                   |            |
| Head Style:   |            |
| Double hexagon w/hole                                   |            |
| Head Height:  |            |
| Between 0.224 inches and 0.244 inches                   |            |
| Width Between Flats:                                    |            |
| Between 0.304 inches and 0.313 inches                   |            |
| Extended Washer Diameter:                               |            |
| Between 0.428 inches and 0.438 inches                   |            |
| Extended Washer Thickness:                              |            |
| Between 0.059 inches and 0.079 inches                   |            |
| Grip Diameter:  |            |
| Between 0.2490 inches and 0.2495 inches                 |            |
| Thread Diameter:  |            |
| 0.250 inches  |            |
| Grip Length:  |            |
| Between 1.052 inches and 1.072 inches                   |            |
| Thready Qty Per Inch (tpi):                             |            |
| 28  |            |
| Min. Tensile Strength (psi):                            |            |
| 220000 pounds per square inch                           |            |
| Hardness Rating:  |            |
| 46.0 rockwell c and 50.0 rockwell c                     |            |
| Material:   |            |
| Steel comp xm-13  |            |
| Material Specification:                                 |            |
| Ams 5629 assn standard single material response         |            |
| Surface Treatment:                                      |            |
| Passivate   |            |
| Surface Treatment Specification:                        |            |
| Qq-p-35 federal specification single treatment response | nse        |
| Thread Series Designator:                               |            |
| Unjf  |            |
| Shelf Life:   |            |
| N/a   |            |

N/a

## NSN 5306-01-185-0447

Shear Bolt - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A003b0