NSN 5306-01-185-2203

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-185-2203

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.720 inches and 0.875 inches |
| Fastener Length: |
| Between 0.845 inches and 0.875 inches |
| Head Style: |
| Distorted head |
| Head Height: |
| Between 0.250 inches and 0.260 inches |
| Width Between Flats: |
| Between 0.551 inches and 0.562 inches |
| Locking Feature: |
| Distortions head |
| End Application: |
| Spec item |
| Thread Diameter: |
| 0.375 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 16 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hardness Rating: |
| 32.0 rockwell c and 38.0 rockwell c |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5306-01-185-2203Machine Bolt - Page 2 of 2



Fiig:

A003b0