## NSN 5306-01-185-7090

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-185-7090 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.550 inches and 0.580 inches **Fastener Length:** Between 4.555 inches and 4.575 inches **Head Style:** Hexagon **Head Height:** 0.315 inches **Shank Unthreaded Hole Diameter:** 0.108 inches all holes and 0.113 inches all holes **First Diameter From Head:** Between 0.496 inches and 0.498 inches **Second Diameter From Head:** Between 0.303 inches and 0.313 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 3.865 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 4.000 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 4.255 inches all holes **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-01-185-7090

Externally Relieved Body Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0