NSN 5306-01-185-7096

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-185-7096

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
0.391 inches
Fastener Length:
Between 1.251 inches and 1.281 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 24
24
24 Min. Tensile Strength (psi):
24 Min. Tensile Strength (psi): 160000 pounds per square inch
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 1 class 3 federal specification single treatment response
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads 32.0 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads 32.0 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads 32.0 microinches thr
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads 32.7 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416 type 1 class 3 federal specification single treatment response
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c_and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads 32.0 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c 30.0 rockwell c 30.0 rockwell c and 40.0 rockwell c 30.0 ro
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.0 microinches threads Material: 32.0 microinches threads 32.0 microinches thr
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads 32.7 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads 32.6 microinches threads
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads 32.0 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads Material: 32.6 microinches threads 32.6 microinches threads

NSN 5306-01-185-7096

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

