

View Online at <https://aerobasegroup.com/nsn/5306-01-185-8659>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.353 inches

**Fastener Length:**

Between 1.026 inches and 1.056 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.186 inches and 0.206 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.340 inches and 0.350 inches

**Extended Washer Thickness:**

Between 0.054 inches and 0.074 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.678 inches and 0.698 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 type 2 class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.