

View Online at <https://aerobasegroup.com/nsn/5306-01-185-8661>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.475 inches and 0.525 inches

Fastener Length:

Between 1.485 inches and 1.515 inches

Head Style:

Double hexagon w/hole

Head Height:

0.234 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.438 inches

Extended Washer Thickness:

0.069 inches

Hole Diameter:

Between 0.034 inches and 0.042 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.990 inches and 1.000 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0