NSN 5306-01-186-1227

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-186-1227 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.385 inches **Fastener Length:** Between 3.365 inches and 3.385 inches **Head Style:** Spline drive shear head **Head Height:** Between 0.177 inches and 0.197 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Head Minor Diameter:** Between 0.514 inches and 0.521 inches **End Application:** Aircraft, hornet f/a-18 **Thread Diameter:** 0.312 inches **Grip Length:** Between 2.990 inches and 3.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.243 inches first hole and 3.277 inches first hole Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-186-1227

Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0