NSN 5306-01-186-2161

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-186-2161

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 0.996 inches and 1.026 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole and 0.080 inches first hole
Thread Diameter:
0.190 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6403 professional/industrial association standard

NSN 5306-01-186-2161

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0