NSN 5306-01-186-3448

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-186-3448 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.690 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Hexagon **Head Height:** Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches **Locking Feature:** Patch threads or strip threads **Thread Diameter:** 0.500 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 150000 pounds per square inch

Hardness Rating:

32.0 rockwell c fastener and 38.0 rockwell c fastener

Special Features:

Locking feature is plastic polyamide

Material:

Steel

Material Specification:

Sae j429, grade 8 assn standard single material response fastener or astm a354, grade bd assn standard single material response fastener

Surface Treatment:

Zinc fastener and chromate fastener

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-01-186-3448 Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0