

View Online at <https://aerobasegroup.com/nsn/5306-01-187-6065>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.564 inches and 0.619 inches

**Fastener Length:**

Between 1.204 inches and 1.234 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.204 inches and 0.234 inches

**Width Between Flats:**

Between 0.678 inches and 0.690 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Single Shear Strength:**

95000 pounds per square inch

**Thread Diameter:**

0.437 inches

**Grip Length:**

Between 0.615 inches and 0.640 inches

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6706 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0