NSN 5306-01-187-6066

Shear Bolt - Page 1 of 2

3

View Online at https://aerobasegroup.com/nsn/5306-01-187-6066



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.345 inches and 0.395 inches Fastener Length: Between 1.543 inches and 1.573 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Hole Diameter: Between 0.046 inches and 0.056 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches Grip Length: Between 1.178 inches and 1.198 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon corners Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

NSN 5306-01-187-6066

Shear Bolt - Page 2 of 2



Thread Series Designator:

Unjf

Specification Data:

80205-nas6304 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0