

View Online at <https://aerobasegroup.com/nsn/5306-01-187-9044>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.629 inches

Fastener Length:

Between 1.754 inches and 1.794 inches

Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Shoulder Diameter:

0.495 inches first shoulder and 0.499 inches first shoulder

Shoulder Length:

1.135 inches first shoulder and 1.155 inches first shoulder

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

13600 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military specification single material response or mil-s-6098 military specification single material response or mil-s-6758 military specification single material response or ams 6300 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1297 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.