## NSN 5306-01-188-4764

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-188-4764

Thread Class:
3a
Thread Direction:
Right-hand  Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:  Between 0.667 inches and 0.697 inches
Head Style:
Dished hexagon  Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Quantity:
3
Hole Type:  Drilled
Thready Qty Per Inch (tpi):
28 Min Tanaila Strongth (nai).
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Chromate and cadmium
Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5306-01-188-4764

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas6304 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: