

View Online at <https://aerobasegroup.com/nsn/5306-01-188-5168>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 3.573 inches and 3.603 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 3.240 inches and 3.260 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.400 inches first hole and 3.450 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Titanium alloy

**Material Specification:**

Ams4967 comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas673 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0