

View Online at <https://aerobasegroup.com/nsn/5306-01-188-5777>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.528 inches

**Fastener Length:**

Between 2.138 inches and 2.168 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.250 inches and 0.265 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Grip Diameter:**

Between 0.4990 inches and 0.4995 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Thread Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.945 inches first hole and 1.965 inches first hole

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928, 6al-4v assn standard single material response or ams 4967, 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6408 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0