NSN 5306-01-188-8362

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-188-8362

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| Between 0.611 inches and 0.641 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.156 inches and 0.171 inches |
| Width Between Flats: |
| Between 0.492 inches and 0.502 inches |
| Hole Diameter: |
| Between 0.070 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.3115 inches and 0.3120 inches |
| Thread Diameter: |
| 0.3125 inches |
| Grip Length: |
| Between 0.178 inches and 0.198 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas6405 professional/industrial association standard |
| Shelf Life: |
| N/a |

NSN 5306-01-188-8362

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

