

View Online at <https://aerobasegroup.com/nsn/5306-01-188-8401>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.454 inches

**Fastener Length:**

Between 3.939 inches and 3.969 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 3.490 inches and 3.501 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.766 inches first hole and 3.776 inches first hole

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6406 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0