## NSN 5306-01-188-8404

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-188-8404

View Online at https://aerobasegroup.com/nsn/5306-01-188-8404
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.454 inches
Fastener Length:
Between 4.314 inches and 4.344 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole and 0.080 inches first hole
Thread Diameter:
0.3750 inches
Grip Length:
Between 3.865 inches and 3.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
4.141 inches first hole and 4.151 inches first hole
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6406 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5306-01-188-8404

Shear Bolt - Page 2 of 2

Fiig: A003b0

