## NSN 5306-01-188-9174

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-188-9174

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.794 inches and 0.824 inches                     |
| Fastener Length:  |
| Between 1.111 inches and 1.131 inches                     |
| Head Style:   |
| Double hexagon w/hole                                     |
| Head Height:  |
| Between 0.373 inches and 0.393 inches                     |
| Width Between Flats:                                      |
| 0.438 inches  |
| Extended Washer Diameter:                                 |
| Between 0.552 inches and 0.572 inches                     |
| Extended Washer Thickness:                                |
| Between 0.090 inches and 0.100 inches                     |
| Hole Diameter:  |
| Between 0.060 inches and 0.080 inches                     |
| Grip Diameter:  |
| Between 0.3740 inches and 0.3745 inches                   |
| Thread Diameter:  |
| 0.375 inches  |
| Grip Length:  |
| Between 0.307 inches and 0.317 inches                     |
| Hole Quantity:  |
| 1   |
| Hole Type:  |
| Drilled   |
| Thready Qty Per Inch (tpi):                               |
| 24  |
| Hole Configuration Style:                                 |
| Double hexagon longitudinal hole                          |
| Surface Finish:   |
| 32.0 microinches threads                                  |
| Material:   |
| Nickel alloy 718  |
| Material Specification:                                   |
| C50tf13 cl-b, fscm 07482 mfr ref single material response |
| Thread Series Designator:                                 |
| Unjf  |

## NSN 5306-01-188-9174

Close Tolerance Bolt - Page 2 of 2



|  |  | ife: |  |
|--|--|------|--|
|  |  |      |  |
|  |  |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0