## NSN 5306-01-189-0014

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-189-0014

80205-nas6603 professional/industrial association standard

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.345 inches  |
| Fastener Length:  |
| Between 0.897 inches and 0.917 inches   |
| Head Style:   |
| Dished hexagon  |
| Head Height:  |
| Between 0.110 inches and 0.125 inches   |
| Width Between Flats:  |
| Between 0.367 inches and 0.376 inches   |
| Hole Diameter:  |
| Between 0.070 inches and 0.080 inches   |
| Grip Diameter:  |
| Between 0.1885 inches and 0.1895 inches   |
| Thread Diameter:  |
| 0.190 inches  |
| Grip Length:  |
| Between 0.552 inches and 0.562 inches   |
| Hole Quantity:  |
| 1   |
| Hole Type:  |
| Drilled   |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Hole Configuration Style:   |
| Round   |
| Material:   |
| Steel comp 4340 or steel comp 8740  |
| Material Specification:   |
| Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard |
| 2nd material response   |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Qq-p-416a federal specification single treatment response   |
| Thread Series Designator:   |
| Unjf  |
| Specification Data:   |

## NSN 5306-01-189-0014

Shear Bolt - Page 2 of 2



| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
|                   |
| No                |
| No Fiig:          |

Mil-std (military Standard):

Mil-s-5000 spec.

Shelf Life: