

View Online at <https://aerobasegroup.com/nsn/5306-01-189-3773>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.510 inches and 0.686 inches

Fastener Length:

Between 2.786 inches and 2.806 inches

Head Style:

Dished hexagon

Head Height:

Between 0.282 inches and 0.297 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Locking Feature:

Detent ring grip

Grip Diameter:

Between 0.5607 inches and 0.5616 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 2.000 inches and 2.016 inches

Thready Qty Per Inch (tpi):

18

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.661 inches first hole and 2.691 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0