NSN 5306-01-189-5393

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-189-5393

view Offilite at https://aerobasegroup.com/hish/3300-01-103-3333
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.463 inches
Fastener Length:
Between 1.391 inches and 1.431 inches
Head Style:
Hexagon
Head Height:
Between 0.172 inches and 0.204 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Shoulder Diameter:
0.309 inches first shoulder and 0.312 inches first shoulder
Shoulder Length:
0.948 inches first shoulder and 0.968 inches first shoulder
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp 4140 or steel comp 8630 or steel comp 8740 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1297 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-189-5393

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0