NSN 5306-01-189-5858

Shear Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-189-5858

Thread Direction: Right-hand Thread Length: 0.528 inches Fastener Length: Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Oty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response Thread Series Designator:
Right-hand Thread Length: 0.528 inches Fastener Length: Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Length: 0.528 inches Fastener Length: Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ans4928 assn standard single material response or ams4967 assn standard single material response
Fastener Length: Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Fastener Length: Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Between 1.575 inches and 1.605 inches Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Head Style: Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Dished hexagon Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Head Height: Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Width Between Flats: Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Between 0.741 inches and 0.752 inches Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Grip Diameter: Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Between 0.4990 inches and 0.4995 inches Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Diameter: 0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
0.5000 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Min. Tensile Strength (psi): 160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
160000 pounds per square inch Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Material: Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Titanium alloy Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Material Specification: Ams4928 assn standard single material response or ams4967 assn standard single material response
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6408 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0