## NSN 5306-01-189-5859

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-189-5859

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.454 inches and 0.474 inches
Fastener Length:
Between 1.392 inches and 1.422 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-189-5859

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas6705 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0