

View Online at <https://aerobasegroup.com/nsn/5306-01-190-2181>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 0.948 inches and 0.978 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Shoulder Diameter:**

0.2490 inches first shoulder and 0.2495 inches first shoulder

**Shoulder Length:**

0.615 inches first shoulder and 0.635 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.775 inches first hole and 0.825 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0