

View Online at <https://aerobasegroup.com/nsn/5306-01-190-4582>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.027 inches and 1.077 inches

**Fastener Length:**

Between 2.662 inches and 2.692 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.472 inches and 0.512 inches

**Extended Washer Diameter:**

Between 1.384 inches and 1.394 inches

**Extended Washer Thickness:**

Between 0.098 inches and 0.118 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Head Minor Diameter:**

Between 0.904 inches and 0.912 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Spline

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0