## NSN 5306-01-190-4582

Shear Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-190-4582

Thread Direction:
Right-hand
Thread Length:
Between 1.027 inches and 1.077 inches
Fastener Length:
Between 2.662 inches and 2.692 inches
Head Style:
Spline extended washer
Head Height:
Between 0.472 inches and 0.512 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
Between 0.098 inches and 0.118 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Head Minor Diameter:
Between 0.904 inches and 0.912 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response

**Surface Treatment:** 

Passivate

## NSN 5306-01-190-4582

Shear Bolt - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0